

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>A61B 18/20</b>		A1	(11) International Publication Number: <b>WO 00/54686</b>
			(43) International Publication Date: 21 September 2000 (21.09.00)
(21) International Application Number: <b>PCT/US00/06619</b>		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 14 March 2000 (14.03.00)		Published With international search report.	
(30) Priority Data:			
60/124,709 15 March 1999 (15.03.99) US			
Not furnished 13 March 2000 (13.03.00) US			
(71) Applicant: ALTUS MEDICAL, INC. [US/US]; Suite B, 1181 Chess Drive, Foster City, CA 94040 (US).			
(72) Inventors: CONNORS, Kevin, P.; 1437A Jefferson Street, San Francisco, CA 94123 (US). SASNETT, Michael, W.; 375 Anita Avenue, Los Altos, CA 94024 (US).			
(74) Agents: HANN, James, F. et al.; Townsend and Townsend and Crew LLP, 8th Floor, Two Embarcadero Center, San Francisco, CA 94111-3834 (US).			

(54) Title: RADIATION DELIVERY MODULE AND DERMAL TISSUE TREATMENT METHOD

## (57) Abstract

A radiation delivery module (8) includes a body (48) supportable on a patient's skin and defines a skin surface plane generally aligned with the patient's skin surface (40). A radiation source (22) is mounted to the body and produces a beam (34) of tissue-damaging radiation directed transverse to and at the skin surface plane. The radiation beam creates a radiation spot (42) having a length (36) and a width (44) at the skin surface plane, the length being at least about 5 to 10 times the width. A number of scanned diode laser radiation sub-sources (64) each directing a radiation beam component (66) at the radiation spot may be used. The radiation source may include a rod lens as a focusing optical element. The radiation delivery module may also include a radiation source translator (18) so that the radiation spot moves in a direction generally perpendicular to the length of the radiation spot.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Licchtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## RADIATION DELIVERY MODULE AND DERMAL TISSUE TREATMENT METHOD

### BACKGROUND OF THE INVENTION

Use of light to denature very specific kinds of tissue has been called wavelength-selective photo-thermolysis. The use of lasers for this purpose has been well described in the literature. See, for example, R.G. Wheland, "Laser-assisted hair removal", Lasers in Dermatology, Vol. 15, pp. 469-477, and references cited. By choosing a laser with the right wavelength and energy per unit area (fluence), a particular light-absorbing target substance (chromophore) in living tissue, such as melanin or possibly hemoglobin, will absorb energy from the treatment beam and become hot enough to destroy functionality in the tissue containing the chromophore. Tissue in the same area that does not have high concentration of the target chromophore will not be as affected.

Hair H, see Fig. 1C, includes two basic parts, the shaft S, which is the portion of the hair above the epidermis E, and the root R, which is the portion below the surface of the epidermis. Various tissues surround the root of the hair. Hair color is primarily due to the presence of melanin in the hair. Melanin is created at the base of the hair follicle F and is passed into the hair as it grows. The presence of melanin has made it possible to use certain lasers and other light sources for hair removal with melanin as the target chromophore. The hair follicle and surrounding structure (referred to collectively as hair tissue T) are selectively heated when the melanin in the hair tissue and in the hair root itself and is exposed to treatment radiation. The hair tissue is thermally damaged as a result of the localized heating after treatment; many of the exposed hairs atrophy and are sloughed from the epidermis.

The early work in this field was centered around a wavelength with very high melanin absorption, the pulsed ruby laser (694nm). Long pulse ruby lasers (as opposed to Q-switched ruby lasers) typically have a pulse duration, or a series of pulses, in the 1 millisecond range. Although the wavelength is highly absorbed in melanin, the wavelength selection has significant limitations with darker skin types as the epidermis can blister or induce a pigmentary change from the superficial melanin heating.

Dermatologists have used cooling devices in dermatologic applications prior to laser treatment. The purpose is to chill the skin with the understanding that exposure to treatment radiation will elevate the epidermal temperature. Chilling lowers

the initial temperature so that the post treatment temperature at the epidermis will not create a heat-induced blister or pigmentary change. U.S. Patent 5,735,844 describes apparatus which uses a cooled lens, through which radiation passes, pressed against the patient's skin to cool the epidermis.

5 Many different approaches to hair removal have been explored since the early ruby laser evaluation. A common trend is a continual shift towards longer wavelengths, which have less melanin absorption, as it allows treatment of patients with a darker range of skin tones. Initially, alexandrite (755nm) was evaluated and later a diode approach (810nm). The alexandrite laser offers some improved clinical capabilities over  
10 the ruby laser if one considers treatment of darker skin types. However, from engineering and system performance measures, the two systems are similar in terms of size, utility requirement, treatment speed, and system cost. In contrast, the high pulse energy diode laser allows the system to be much smaller than previous systems with an ability to run off of standard power. A high pulse energy diode has many attractive attributes over  
15 other laser approaches, such as flashlamp excited solid-state devices and therapeutic filtered flashlamps. One of the most desirable traits is the high efficiency associated with diode generated laser radiation. As a result of improved efficiency, the system can be smaller and lighter weight.

One of the performance limitations working against a diode laser for an  
20 application like hair removal is the need for high peak power for short bursts. In general, diode lasers may be pulsed at peak power levels higher than the rated continuous power. However, the peak rating is not a significantly higher power level (perhaps two to three times) than the continuous level. A constraint that a hair removal application has is the need to deliver significant energy deep into the dermis to sufficiently heat the hair tissue  
25 to induce a thermal injury so that the hair will slough off. Light scatters as it propagates through the tissue. As a result of this severe exposure, large area treatments (greater than 20 mm<sup>2</sup>) have been explored to overcome the reduction (due to scatter) in intensity as the light travels deeper into the dermis. A large treatment area can generate a fairly homogeneous intensity profile under the center of the treatment area as light propagates  
30 into the dermis.

A commercially-available diode laser system for hair removal is sold by Coherent of Santa Clara, California as Lightsheer and allows the physician to treat the darker skin types than ruby lasers with a lower risk of post operative blistering. The Lightsheer system employs many diode bars (between 50 to 100) to create high peak

power (2-4 kW) and a large square treatment area (about  $.81\text{cm}^2$ ). The Lightsheer system is used in pulsed operation with treatment rates up to about  $1.6\text{cm}^2/\text{sec}$ . The system has a pulse duration between 5 and 30 ms, which closely matches the thermal relaxation time of typical hair follicles.

## SUMMARY OF THE INVENTION

5 A radiation delivery module includes a body supportable on a skin surface of a patient to define a skin surface plane. A radiation source is mounted to the body and produces a beam of tissue-damaging radiation directed transverse to and at the skin surface plane. The radiation beams creates a radiation spot having a length and a width at  
10 the skin contacting plane, the length preferably being about 10 or more times, but at least about 5 times, the width. A number of radiation sources, each directing a radiation beam component at the radiation spot, may be used. The radiation source may include a rod lens as a focusing optical element. The radiation delivery module may also include means for translating the radiation source so that the radiation spot moves in a direction  
15 generally perpendicular to the length of the radiation spot.

Another aspect of the invention relates to a method for treating dermal tissue. A tissue-damaging radiation beam is directed the skin of a patient to create a radiation spot on the skin having a length of preferably about 10 or more times, but at least about 5 times, its width. The radiation beam is moved along the skin in a direction  
20 transversed to the length. The directing step may be carried out with the radiation beam having a focal point located below the skin surface. The radiation beam is preferably moved in a direction which is perpendicular to the length of the radiation spot. The invention may be carried out using a radiation delivery module, including a body carrying a translatable radiation source, positioned at a chosen location on the skin surface of the  
25 patient. The radiation source may be moved relative to the body while the body is stationary relative to the skin surface. A number of radiation sub-sources, each producing a radiation beam component, may be used to produce the radiation beam. The radiation beam may be produced using a diode laser.

Other features and advantages of the invention will appear from the  
30 following description in which the preferred embodiment has been set forth in detail in conjunction with the accompanying drawings.

## BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a simplified schematic view of a radiation delivery system made according to the invention;

Fig. 1A and 1B are schematic representations of the main components of the system console and the radiation delivery module of Fig. 1;

Fig. 1C is a simplified cross-sectional view of a hair with its root within a hair follicle;

Fig. 2 illustrates, in simplified form, an overall view of the radiation delivery module of Fig. 1 resting on a skin surface of a patient;

Fig. 3 is a simplified view of the main functional components of a radiation source of Fig. 2 including a laser diode and a focusing rod lens which creates a focal point below the skin surface and creates a elongate rectangular radiation spot having a length about 10 times the width on the skin surface; and

Fig. 4 is a simplified view illustrating a number of radiation sub-sources which constitute the radiation source of Fig. 2 and a mechanical radiation source translator which permits the radiation spot to be controllably translated along the skin surface.

## DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Figs. 1, 1A and 1B illustrate a radiation delivery system 2 in schematic form. System 2 includes broadly a system console 4 coupled to a power source 6, and a radiation delivery module 8 coupled to system consoles 4 by an umbilical cable 10. System console 4 can be generally conventional in construction and typically includes an AC power distribution module 12, a high current diode power supply 14, a thermoelectric cooler drive circuit 16, a user interface 17 and control electronics 19. The components of system console 4 are typically generally conventional in construction, form no part of this invention and will not be described further.

Fig. 1B illustrates in schematic form radiation delivery module 8 seen to include a radiation source translator 18, an epidermal cooling unit 20 (not shown in any other figure), and four components constituting the radiation source 22 shown in Fig. 2. Radiation source 22 includes a number of laser diodes 24, beam conditioning optics 26, diode cooling unit 28 (shown only in Fig. 1B), and safety shutter 30 (shown only in Fig. 1B). While in the preferred embodiment several laser diodes are used, to simplify the discussion, Figs. 1B, 2 and 3 will be discussed with reference to only a single laser diode.

Radiation source translator 18 is used to control the dwell time on tissue. Cooling of the patient's skin before and/or after being irradiated by epidermal cooling unit 20 can help prevent undesirable tissue damage and reduce pain. Examples of cooling surfaces can be found at U.S. Patent No. 5,735,844 and disclosed in U.S. Patent Application No. 09/393,830.

Diode cooling unit 28 is used to remove the heat created by laser diodes 24, and typically includes a Peltier cooling device in close proximity to the diode device(s). Alternatively, forced air in conjunction with a diode-mounted heat fin can function as the cooling unit.

Safety shutter 30 is used to ensure no unexpected radiation exposure when the laser system is in the "off" or "standby" state.

With reference now to Figs. 2 and 3, radiation source 22 is seen to include a laser diode 24 and a cylinder lens 32, the cylinder lens functioning as a main component of the conditioning optics 26. Laser diode 24 is illustrated as a single component for ease of illustration. Laser diode 24 has a length 36 and creates a focal line 38 situated below skin surface 40 so to create a radiation spot 42 at skin surface 40. Radiation spot 42 has a width 44 and has generally the same length, that is length 36, as laser diode 24. Radiation spot 42 preferably has a length to width ratio of at least about 10 to 1, but at least about 5 to 1. By creating a relatively long, narrow radiation spot and by translating the radiation spot perpendicular to its length, the non-therapeutic regions created by radiation beam 34 are minimized. In this way, the problems associated with radiation beam scatter, which includes ineffective heating of the target zone, such as target tissue T, can be substantially reduced. Most radiation scattered parallel to length 36 remains within the heating zone beneath spot 42. Most radiation scattered perpendicular to length 36 heats tissue which has just passed under spot 42 or which will soon pass under spot 42. The regions perpendicular to the length of radiation spot 42, except at the very start and stop of movement, are subjected to full radiation intensity as the beam moves forward. Only at the ends 46 of radiation spot 42 will there be therapeutically ineffective radiation zones such that that tissue is heated but not to a therapeutically effective extent. However, the aggregate area of such ineffectively treated radiation zones are minimized by the configuration and movement of the present invention. Of course during subsequent movements of radiation source 22, those ineffectively treated radiation zones along the edges 46 of radiation spot 42 can be properly heated and treated.



In the present invention it is preferred that radiation source 22 be carried within a housing or body 48, the body having a circumferential skin contacting edge 50 which defines a skin surface plane. Skin surface 40 is assumed to be generally coincident with the skin surface plane. When radiation spot 42 is properly positioned on skin surface 40, radiation source 22 is translated by radiation source translator 18, shown in Fig. 4. Translator 18 includes, for example, a lead screw 54 passing through a threaded boss 56 extending from radiation source 22 and also through an internally threaded drive nut 58. Drive nut 58 is rotated by a drive gear 60. Both lead screw 54 and drive nut 58 are restrained from moving axially but free to rotate so that rotating drive gear 60 rotates drive nut 58 thus causing lead screw 54 to rotate. This rotation of lead screw 54 causes radiation source 22 to move or translate in the direction of arrow 62. Radiation source 22 of Fig. 4 also is shown to include a number, in this case five, radiation sub-sources 64 each with its own radiation beam component 66, components 66 combining to create radiation beam 34.

Translator 18 may also use a stepper motor, a linear driver, belts and pulleys, a rack and pinion, a linear induction motor or any other conventional or unconventional structure to translate radiation source 18. In addition, translation of radiation source 22 may also be provided by moving body 48 with radiation source 22 housed therein across skin surface 40.

Before beginning treatment, for example hair removal treatment, skin surface 40 may be marked with lines, dots or other markings to help guide placement of radiation delivery module 8 on the skin surface 40. Skin contacting edge 50 of body 48 is placed on skin surface 40 typically with radiation source 22 at one end of body 48. Once properly positioned the user can begin treatment by entering the proper information using user interface 18. This information may include, for example, hair color, skin color and typical hair shaft diameter. Radiation source 22 is then energized and translator 52 is operated to cause radiation source to move in the direction of arrow 62 over skin surface 40, that is in a direction generally perpendicular to length 36, while irradiating the skin surface along radiation spot 42. After the end of a pass, radiation source 22 can be moved in the opposite direction using transducer 52 if necessary or desired. Radiation spot 42 typically will not extend the full width of body 48 nor traverse the full length of the body. The therapeutically effectively irradiated region may be shown by alignment marks 68 on body 48, see Fig. 2, to help properly align body 48 when an adjacent section of skin surface 40 is to be irradiated.

Effectively controlling the pulse duration as seen by a cross section of dermis requires the dwell time to be controlled. Width 44 and the translation speed will determine the effective pulse duration. The fluence will be determined by the intensity of radiation source 22 within this dimension. Pulse duration can be controlled by, for  
5 example, scanning at varied rates.

Modification and variation can be to the disclosed embodiments without departing from the subject invention as defined in the following claims. For example, body 48 may include transparent portions or may be totally transparent. Also, body 48  
10 need not be solid but could be made of mesh and or spaced apart framing members.

Any and all patents, patent applications and printed publications are  
10 incorporated by reference.

WHAT IS CLAIMED IS:

- 1                   1.     A radiation delivery module comprising:  
2                   a body supportable over a skin surface of a patient;  
3                   a radiation source mounted to the body and producing a beam of tissue-  
4     damaging radiation ;  
5                   said radiation beam creating a radiation spot having a length and a width,  
6     said length being at least about 5 times the width.
- 1                   2.     The radiation delivery module according to claim 1 wherein:  
2                   the body defines a skin surface plane;  
3                   the radiation beam is directed transverse to and at the skin surface plane;  
4     and  
5                   the length and width of the radiation spot is measured at the skin surface  
6     plane.
- 1                   3.     The radiation delivery module according to claim 1 wherein the  
2     length of the radiation spot is at least about 10 times the width.
- 1                   4.     The radiation delivery module according to claim 1 comprising a  
2     plurality of radiation sub-sources each creating a radiation beam component.
- 1                   5.     The radiation delivery module according to claim 1 wherein the  
2     radiation source comprises a cylinder lens as a focusing optical element.
- 1                   6.     The radiation delivery module according to claim 1 wherein the  
2     radiation source comprises a diode laser source.
- 1                   7.     The radiation delivery module according to claim 1 further  
2     comprising means for translating said radiation source within said body so said radiation  
3     spot moves in a direction generally perpendicular to said length.
- 1                   8.     A radiation delivery module comprising:  
2                   a body supportable over a skin surface of a patient and defining a skin  
3     surface plane;  
4                   a radiation source mounted to the body, the radiation source comprising a  
5     plurality of diode laser radiation sub-sources each creating a radiation beam component,

6 said radiation beam components combining to produce a beam of tissue-damaging  
7 radiation directed transverse to and at the skin surface plane; and  
8 said radiation beam creating a radiation spot having a length and a width at  
9 the skin-contacting plane, said length being at least about 10 times the width.

1 9. A method for treating dermal tissue comprising:  
2 directing a tissue-damaging radiation beam at the skin of a patient to create  
3 a radiation spot on the skin having a length and width, the length being at least about 5  
4 times the width;  
5 moving the radiation beam along the skin in a direction transverse to the  
6 radiation spot length.

1 10. The method according to claim 9 wherein the directing step is  
2 carried out with the radiation beam having a focal point located below the skin surface.

1 11. The method according to claim 9 wherein the directing step is  
2 carried out with a radiation beam having a radiation spot with the length being at least  
3 about 10 times the width.

1 12. The method according to claim 9 wherein the moving step is  
2 carried out with the direction being perpendicular to the length of the radiation spot.

1 13. The method according to claim 9 further comprising positioning a  
2 radiation delivery module, comprising a body carrying a translatable radiation source, at a  
3 chosen location on the skin of a patient, the radiation beam produced by the radiation  
4 source.

1 14. The method according to claim 13 wherein the moving step  
2 comprises moving the radiation source relative to the body while maintaining the body  
3 stationary relative to the skin.

1 15. The method according to claim 9 wherein the directing step is  
2 carried out using a plurality of radiation sub-sources each producing a radiation beam  
3 component.

1 16. The method according to claim 9 wherein the directing step is  
2 carried out using a diode laser.

- 1                   17. A method for treating dermal tissue comprising:  
2                   positioning a radiation delivery module, comprising a body carrying a  
3 translatable scanned diode laser radiation source, at a chosen location on the skin surface  
4 of a patient, the radiation source comprising a plurality of radiation sub-sources each  
5 producing a radiation beam component;  
6                   directing a tissue-damaging radiation beam from the radiation source at the  
7 skin of a patient to create a radiation spot on the skin having a length and width, the  
8 length being at least about 10 times the width; and  
9                   moving the radiation beam relative to the body and along the skin in a  
10 direction perpendicular to the radiation spot length while maintaining the body stationary  
11 relative to the skin.

1 / 5




FIG. 1




FIG. 1A

2 / 5




FIG. 1B

3 / 5




FIG. 1C



4 / 5






FIG. 2

5 / 5



## INTERNATIONAL SEARCH REPORT

Int. l. Application No.

PCT/US 00/06619

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 A61B18/20

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 51235 A (GEN HOSPITAL CORP ; PALOMAR MEDICAL TECHNOLOGIES I (US)) 19 November 1998 (1998-11-19)	1-6, 8-13, 15, 16
A	page 7, line 26 - line 28 page 19, line 31 - page 20, line 7; figures 9, 10A	7, 14, 17
X	WO 96 22813 A (CANDELA LASER CORP.) 1 August 1996 (1996-08-01)	1, 3, 9, 11
A	page 6, line 12 - line 16; figure 3	
A	US 5 820 625 A (IZAWA YOSHIHIRO ET AL) 13 October 1998 (1998-10-13)	1, 4, 6, 9, 15, 16
A	column 5, line 17 - line 31; figure 1	
A	EP 0 736 308 A (ESC MEDICAL SYSTEMS LTD) 9 October 1996 (1996-10-09)	1, 8, 9, 17
	column 8, line 22 - line 31; figures 3, 4	
	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&amp;" document member of the same patent family

Date of the actual completion of the international search

28 June 2000

Date of mailing of the international search report

04/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3018

Authorized officer

Mayer, E

# INTERNATIONAL SEARCH REPORT

Int. l. Application No.

PCT/US 00/06619

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 474 549 A (ORTIZ MARK V ET AL) 12 December 1995 (1995-12-12) column 4, line 20 - line 29; figure 2	7, 14, 17

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/06619

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9851235 A	19-11-1998	AU 7568698 A EP 0991372 A	08-12-1998 12-04-2000
WO 9622813 A	01-08-1996	US 5599342 A AU 4686296 A	04-02-1997 14-08-1996
US 5820625 A	13-10-1998	AU 696920 B AU 1892897 A CA 2203223 A ES 2123461 A IT MI970954 A	24-09-1998 02-04-1998 26-03-1998 01-01-1999 26-10-1998
EP 0736308 A	09-10-1996	US 5683380 A AU 717203 B AU 4817496 A CA 2171260 A DE 29623504 U FI 961413 A JP 8266326 A US 5885273 A	04-11-1997 23-03-2000 10-10-1996 30-09-1996 20-08-1998 30-09-1996 15-10-1996 23-03-1999
US 5474549 A	12-12-1995	NONE	